

POCKET COLLECTION


SPECIFICATIONS

- 120V INPUT VOLTAGE, 50/60Hz
- HIGH POWER FACTOR
- AMBIENT OPERATING TEMPERATURE -40°C (-40°F) TO +50°C (122°F)
- ESTIMATED 50,000 HRS L₇₀*
- 5 YEAR WARRANTY
- DIMMABLE
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT RESINS
- ACRYLIC DIFFUSER
- UL LISTED FOR WET LOCATIONS
- COTTAGE FIXTURE (FP120) LISTED FOR DAMP LOCATIONS
- STANDARD PACK QTY: 6




FP120

EXTENDS: 4 3/4"
HCMT: 6"




FP123

EXTENDS: 7"
HCMT: 4 1/4"



FP133

EXTENDS: 5 3/4"
HCMT: 2 3/8"



RoHS
compliant

PATENT PENDING
EOS LIGHT ENGINE

EXAMPLE # FP103-LE800C-BCP

STYLE #	SOURCE/WATTAGE	LUMENS/CCT	BODY	LENS	OPTIONS
FP120 = COTTAGE	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	★ W = 900lm 3000K C = 1000lm 4000K	B = BLACK	W = WHITE	P = PHOTOCELL
FP123 = ACORN	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	★ W = 900lm 3000K C = 1000lm 4000K	B = BLACK W = WHITE	W = WHITE	P = PHOTOCELL
FP133 = BUNGALO	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	★ W = 900lm 3000K C = 1000lm 4000K	B = BLACK W = WHITE	C = CLEAR FLEMISH	P = PHOTOCELL

LE800 LED REPLACEMENT PARTS	
L08-AC120R-W	= 900 LUMEN 3000K ARRAY
L08-AC120R-C	= 1000 LUMEN 4000K ARRAY

* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

** ESTIMATED FROM LED SOURCE



PROlite LED Lighting™

A Division of Emergence® Lighting, Inc.